

DHB-E SLi SERIES

multi-point 3 phase

The DHB-E SLi electronic unit offers all the major comfort settings of any electronically controlled instantaneous water heater. An actively-controlled heating output compensates for pressure fluctuations in the water supply, guaranteeing a pleasant shower experience. With advanced electronics, it consumes up to 30% less energy and water.

- Constant temperature to the output limit
- Infinitely variable temperature adjustment within range
- Exclusive soft-line design
- Electronic Safety system with air detection
- For Hard and Soft water areas
- Bare wire heating system with pressure-tested copper casing



Technical Data

Temperature Adjustment: 30°C to 60°C

Dimensions (HxWxD): 478 x 225 x 205 (mm)

Colour: White

Weight: 5.20 kg

Power Supply: 3/PE 400V 50Hz

IP-rating (Hoseproof): IP25

Max Pressure: 10 bar

Inlet Size: G 1/2"

DHB-E 13 SLi

13.5 kW **Rated Output**

19 A **Rated Current**

20 A **Recommended Circuit Breaker**

3/PE 400V 50Hz **Power Supply**

4 mm² **Wire Size**

DHB-E 18 SLi 25A

18 kW **Rated Output**

26 A **Rated Current**

25 A **Recommended Circuit Breaker**

3/PE 400V 50Hz **Power Supply**

6 mm² **Wire Size**

DHB-E 18/21/24 SLi

18/21/24 kW (Selectable) **Rated Output**

29/31/35 A **Rated Current**

40 A **Recommended Circuit Breaker**

3/PE 400V 50Hz **Power Supply**

6 mm² **Wire Size**

DHB-E 27 SLi

27 kW **Rated Output**

39 A **Rated Current**

40 A **Recommended Circuit Breaker**

3/PE 400V 50Hz **Power Supply**

6 mm² **Wire Size**

