

# DHB-E 13 SLi

CONVENIENCE INSTANTANEOUS WATER  
HEATER

PRODUCT-NO.: 232014

On the DHB-E SL instantaneous water heater, the water temperature is continuously electronically controlled by three sensors with 3i technology. This makes temperature fluctuations a thing of the past and guarantees accurate temperature delivery right up to maximum output – for enjoyable showers.

With its high efficiency and output, the DHB-E SL instantaneous water heater offers reliable functionality for constant hot water. The rotary selector quickly enables accurate temperature delivery between 30 and 60 °C.



## The main features

Electronically controlled instantaneous water heater

---

3i technology for maximum energy efficiency and accurate temperature delivery

---

Variable temperature selection

---

Anti-scalding protection (43 °C) can be permanently activated



Type	DHB-E 18/21/24 SLi	DHB-E 18 SLi 25A	DHB-E 11 SLi
Part no.	232016	232015	232013
Rated output	18/21/24 kW	18 kW	11 kW
Height	478 mm	478 mm	478 mm
Width	225 mm	225 mm	225 mm
Depth	105 mm	105 mm	105 mm

## Technical data

Rated voltage	400 V	400 V	400 V
Phases	3/PE	3/PE	3/PE
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Rated current	29/31/35 A	26 A	16 A
Fuses	32/32/35 A	25 A	16 A
Temperature adjustment	30 - 60 °C	30 - 60 °C	30 - 60 °C
Specific conductivity $\sigma_{15} \leq$	1111 $\mu\text{S}/\text{cm}$	1111 $\mu\text{S}/\text{cm}$	1111 $\mu\text{S}/\text{cm}$
Specific resistance $\rho_{15} \geq$	900 $\Omega \text{ cm}$	900 $\Omega \text{ cm}$	900 $\Omega \text{ cm}$
Energy efficiency class	A	A	A
Colour	white	white	white
IP-Rating	IP25	IP25	IP25
Weight	3,6 kg	3,6 kg	3,6 kg



Type	DHB-E 13 SLi	DHB-E 27 SLi
Part no.	232014	232017
Rated output	13,5 kW	27 kW
Height	478 mm	478 mm
Width	225 mm	225 mm
Depth	105 mm	105 mm

## Technical data

Rated voltage	400 V	400 V
Phases	3/PE	3/PE
Frequency	50/60 Hz	50/60 Hz
Rated current	19,5 A	39 A
Fuses	20 A	40 A
Temperature adjustment	30 - 60 °C	30 - 60 °C
Specific conductivity $\sigma_{15} \leq$	1111 $\mu\text{S}/\text{cm}$	1111 $\mu\text{S}/\text{cm}$
Specific resistance $\rho_{15} \geq$	900 $\Omega \text{ cm}$	900 $\Omega \text{ cm}$
Energy efficiency class	A	A
Colour	white	white
IP-Rating	IP25	IP25
Weight	3,6 kg	3,6 kg