

DHC 6 XG (STE)

MINI INSTANTANEOUS WATER HEATER

PRODUCT-NO.: 236217

The main features

Phase cycling control for greater convenience

Infinitely variable temperature adjustment up to maximum output via rotary selector

LED ON indicator on the appliance cover provides clear information about appliance status

Tubular heater made of copper for a longer service life

Installation on finished walls is possible

Integrated high limit safety cut-out and RCD for maximum safety

IP 25 for greater protection against water ingress (hoseproof)





Type	DHC 4 XG (STE)	DHC 6 XG (STE)	DHC 8 XG (STE)
Part no.	239628	236217	236218

Technical data

Rated voltage 1	220 V	220 V	220 V
Rated voltage 2	230 V	230 V	230 V
Rated voltage 3	240 V	240 V	240 V
Rated output 1	4,0 kW	6,0 kW	8,0 kW
Rated output 2	4,4 kW	6,6 kW	8,7 kW
Rated output 3	4,8 kW	7,1 kW	9,5 kW
Fuse 1	25 A	32 A	40 A
Fuse 2	25 A	32 A	40 A
Fuse 3	25 A	32 A	40 A
Phases	1/N/PE ~220-240V	1/N/PE ~220-240V	1/N/PE ~220-240V
Type	sealed	sealed	sealed
Max. permissible pressure	1 MPa	1 MPa	1 MPa
Minimum supply pressure	0,018 MPa	0,02 MPa	0,03 MPa
Colour	white	silver	silver
Weight	2 kg	2 kg	2,2 kg